



High performance chemical based anchors made with Vinylester (often referred to as Epoxy Acrylate).

For attaching studs to concrete, brick and stone.

Free from expansion forces.

GLASS SPIN-IN CAPSULES - Vinylester (Epoxy Acrylate)

| Code | Size | Hole Diameter | Capsule Length | Capsule Diameter | Fastens Up To | Min Hole Depth | Qty Per Box | Weight Kg Per 100 | Price £ Per 100 |
|-----------|------|---------------|----------------|------------------|---------------|----------------|-------------|-------------------|-----------------|
| 0868M54SI | M8 | 10 | 80 | 9 | - | 80 | 10 | 1.18 | 130.74 |
| 0868M56SI | M10 | 12 | 80 | 11 | - | 90 | 10 | 1.46 | 140.00 |
| 0868M58SI | M12 | 14 | 95 | 13 | - | 110 | 10 | 2.50 | 159.37 |
| 0868M62SI | M16 | 18 | 95 | 17 | - | 125 | 10 | 3.80 | 199.21 |
| 0868M64SI | M20 | 22 | 175 | 22 | - | 170 | 6 | 12.17 | 316.93 |
| 0868M66SI | M24 | 26 | 210 | 24 | - | 210 | 6 | 16.17 | 398.42 |



Industry standard length Studs, complete with a nut and washer and stud end cut at 45° with hexagon drive.



STUDS - Zinc & Yellow with internal hexagon tool in each box

| Code | Size | Length | Hole Diameter | Fastens Up To | Min Hole Depth | Qty Per Box | Weight Kg Per 100 | Price £ Per 100 |
|-------------|------|--------|---------------|---------------|----------------|-------------|-------------------|-----------------|
| 0868S540110 | M8 | 110 | 10 | 20 | 80 | 10 | 4.50 | 58.72 |
| 0868S560130 | M10 | 130 | 12 | 45 | 90 | 10 | 8.00 | 69.90 |
| 0868S580160 | M12 | 160 | 14 | 35 | 110 | 10 | 13.50 | 99.08 |
| 0868S620190 | M16 | 190 | 18 | 45 | 125 | 10 | 30.00 | 148.61 |
| 0868S640260 | M20 | 260 | 25 | 67 | 170 | 10 | 60.00 | 356.67 |
| 0868S660300 | M24 | 300 | 28 | 65 | 210 | 10 | 110.00 | 607.95 |
| 0868S690380 | M30 | 380 | 35 | 70 | 280 | 5 | 240.00 | 1729.29 |



Industry standard length Studs, complete with a nut and washer and stud end cut at 45° with hexagon drive.

STUDS - Hot Dipped Galvanised with internal hexagon tool in each box


| Code | Size | Length | Hole Diameter | Fastens Up To | Min Hole Depth | Qty Per Box | Weight Kg Per 100 | Price £ Per 100 |
|--------------|------|--------|---------------|---------------|----------------|-------------|-------------------|-----------------|
| 0868S540110G | M8 | 110 | 10 | 20 | 80 | 10 | 4.50 | 127.78 |
| 0868S560130G | M10 | 130 | 12 | 45 | 90 | 10 | 8.00 | 164.36 |
| 0868S580160G | M12 | 160 | 14 | 35 | 110 | 10 | 13.50 | 193.98 |
| 0868S620190G | M16 | 190 | 18 | 45 | 125 | 10 | 30.00 | 300.00 |
| 0868S640260G | M20 | 260 | 25 | 67 | 170 | 10 | 60.00 | 598.29 |
| 0868S660300G | M24 | 300 | 28 | 65 | 210 | 10 | 110.00 | 1109.44 |




Industry standard length Studs, complete with a nut and washer and stud end cut at 45° with hexagon drive.

STUDS - Stainless Steel A2 requires setting tool when used with capsule


| Code | Size | Length | Hole Diameter | Fastens Up To | Min Hole Depth | Qty Per Box | Weight Kg Per 100 | Price £ Per 100 |
|---------------|------|--------|---------------|---------------|----------------|-------------|-------------------|-----------------|
| 0868S540110SS | M8 | 110 | 10 | 20 | 80 | 10 | 4.50 | 157.99 |
| 0868S560130SS | M10 | 130 | 12 | 45 | 90 | 10 | 8.00 | 236.05 |
| 0868S580160SS | M12 | 160 | 14 | 35 | 110 | 10 | 13.50 | 343.32 |
| 0868S620190SS | M16 | 190 | 18 | 45 | 125 | 10 | 30.00 | 628.87 |
| 0868S640260SS | M20 | 260 | 25 | 67 | 170 | 10 | 60.00 | 1197.22 |
| 0868S660300SS | M24 | 300 | 28 | 65 | 210 | 10 | 110.00 | 1766.51 |




Drill your hole to the correct diameter...



...clear any debris...



...insert capsule and spin in the stud...



...allow the recommended cure time.