

PLASTERBOARD FIXINGS - Metal or Nylon

Code	Screw Size	Max Fixture Thickness	Fixing Length	Qty Per Box	Weight Kg Per 100	Price £ Per 100
0866METAL	4.5 x 30	10	38	100	0.91	17.36
0866NYLON	4.5 x 30	10	31	100	0.45	12.12



Metal - extremely efficient and popular for plasterboard.

Nylon - cost effective fixing used for light fixtures into plasterboard.

PLASTERBOARD FIXINGS Open end for variable screw lengths - Metal

Code	Screw Size	Max Fixture Thickness	Fixing Length	Qty Per Box	Weight Kg Per 100	Price £ Per 100
0968T707	4.5 x 37	12	31	100	1.40	26.58
0961T718	4.5 x 45	12	38	100	1.90	66.70



Heavy duty and easy fix with higher load capacity.

NYLON TOGGLE ANCHORS

Code	Woodscrew Size	Screw Gauge	Wall Thickness	Minimum Cavity Depth	Hole Size	Rec Tensile Load Kn	Qty Per Box	Weight Kg Per 100	Price £ Per 100
0863T1012	3.5-4.0	6-8	10-12	30	8	0.12	100	0.23	8.95
0863T1216	3.5-4.0	6-8	12-16	35	8	0.12	100	0.25	9.91
0863T1619	3.5-4.0	6-8	16-19	40	8	0.12	100	0.25	14.22



Medium duty plasterboard fixing used for ceiling fixtures, light shelving or kitchen & bathroom fittings.

RUBBER NUTS - with Brass inserts

Code	Thread Diameter	Hole Diameter	Wall Thickness	Overall Length	Flange Thickness	Flange Diameter	Rec Tightening Torque	Qty Per Box	Weight Kg Per 100	Price £ Per 100
0864M450011	4	8	0.0-2.0	11	1.4	11	1.0	50	0.19	38.02
0864M450025	4	8	6.0-14.0	25	1.4	11	1.0	50	0.30	34.60
0864M470015	5	10	0.0-2.0	15	1.0	13	1.8	50	0.24	40.09
0864M470025	5	10	6.0-14.0	25	1.3	14	1.8	50	0.36	41.47
0864M470040	5	10	19.0-26.0	40	1.3	14	1.8	50	0.40	46.32
0864M490015	6	13	0.0-2.0	15	1.3	16	4.0	50	0.42	51.16
0864M490025	6	13	3.0-13.0	25	2.0	18	4.0	50	0.58	59.44
0864M540025	8	18	6.0-15.0	25	5.7	22	8.0	50	1.12	94.01
0864M540050	8	18	25.0-35.0	50	1.6	20	8.0	50	1.88	113.37
0864M560055	10	20	25.0-35.0	55	1.3	22.5	10.0	50	2.28	135.49
0864M580075	12	24	33.0-45.0	75	1.3	27	15.0	50	4.00	215.67

(loads vary depending on the condition of the base material)



Vibration resistant fixing that can be used in virtually any construction material as the sleeve compresses in irregular holes.

Used in damp and sanitary applications.