

NYLON FRAME FIXINGS

Code	Size	Anchor Hole Size	Anchor Plug Length	Fastens Up To	Min Hole Depth	Rec Tensile kN	Rec Shear kN	Qty Per Box	Qty Per Outer	Weight Kg Per 100	Price £ Per 100
0835M540060	8 x 60	8	60	20	70	0.5	0.5	50	1200	1.29	18.92
0835M540080	8 x 80	8	80	40	90	0.5	0.5	50	1200	1.61	23.96
0835M540100	8 x 100	8	100	50	110	0.5	0.5	50	1100	1.96	25.98
0835M540120	8 x 120	8	120	70	130	0.5	0.5	25	600	2.36	36.25
0835M540135	8 x 135	8	135	85	145	0.5	0.5	25	600	2.70	39.34
0835M560080	10 x 80	10	80	30	90	0.6	0.6	25	600	2.40	34.68
0835M560100	10 x 100	10	100	50	110	0.6	0.6	25	600	3.02	39.34
0835M560115	10 x 115	10	115	65	125	0.6	0.6	20	480	3.88	47.29
0835M560135	10 x 135	10	135	85	145	0.6	0.6	20	480	4.98	55.36
0835M560160	10 x 160	10	160	110	170	0.6	0.6	20	480	5.38	72.12



Long shafted nylon plug for through fixing a wide range of products with a specially matched zinc & yellow screw

Suitable for concrete, full brick and perforated bricks

Pozi Drive
M8 = No3
M10 = No4

HAMMER FIXINGS

Code	Size	Anchor Hole Size	Anchor Plug Length	Fastens Up To	Min Hole Depth	Rec Tensile kN	Rec Shear kN	Qty Per Box	Qty Per Outer	Weight Kg Per 100	Price £ Per 100
0837M470030	5 x 30	5	30	5	40	0.16	0.18	100	3500	0.25	7.16
0837M470045	5 x 45	5	45	15	55	0.18	0.20	100	3500	0.40	7.48
0837M490040	6 x 40	6	40	10	50	0.20	0.20	100	3500	0.38	7.25
0837M490055	6 x 55	6	55	25	65	0.22	0.22	100	2400	0.54	8.76
0837M490070	6 x 70	6	70	40	80	0.22	0.22	100	2400	0.70	11.17
0837M540060	8 x 60	8	60	12	67	0.32	0.30	50	1750	0.94	13.96
0837M540075	8 x 75	8	75	30	85	0.32	0.30	50	1750	1.26	15.23
0837M540100	8 x 100	8	100	60	110	0.32	0.30	50	1200	1.60	23.26
0837M540120	8 x 120	8	120	80	130	0.32	0.30	50	1200	1.92	25.12
0837M540135	8 x 135	8	135	95	145	0.32	0.30	50	1200	2.16	27.64



Recommended where a rapid fix and a large number of fixings are required

This plug can be used for quick installation in internal and external construction work

Suitable for concrete natural stone and solid brick masonry

zinc or stainless steel screws available.


HAMMER FIXINGS - Stainless Steel Screw A2-304

Code	Size	Anchor Hole Size	Anchor Plug Length	Fastens Up To	Min Hole Depth	Rec Tensile kN	Rec Shear kN	Qty Per Box	Weight Kg Per 100	Price £ Per 100
0837M470030SS	5 x 30	5	30	5	40	0.80	0.90	100	0.35	20.56
0837M490040SS	6 x 40	6	40	10	50	1.00	1.00	100	0.47	25.93
0837M490060SS	6 x 60	6	60	30	70	1.10	1.10	100	0.60	31.04
0837M540100SS	8 x 100	8	100	60	110	1.10	1.50	100	1.56	66.55




Ideal for quick installation and with stainless steel screws for added corrosion resistance


Loads are for 25 N/mm² CONCRETE




Drill your hole to the correct diameter...



...clear any debris...



...insert fixing into hole...



...tighten to complete fixing process